

SPACE SAVER CABINET STYLE WATER SOFTENER

RESIDENTIAL WATER SOFTENER

THESE PREMIUM WATER SOFTENING SYSTEMS PROVIDE:

- Compact design perfect for condominiums and small homes with limited space
- Cleaner, safer, better tasting water throughout the home
- Spotless dishes, glassware, tile & faucets
- Soaps and shampoos have richer lather and rinse cleaner
- Softer laundry and reduced detergent usage
- Reduced staining on kitchen and bathroom sinks and tubs
- Reduce wear and tear and maintenance requirements on water appliances
- Better tasting water for drinking, cooking and ice cubes
- Several media types available to meet treatment goals

CLACK WS1 CONTROL VALVE SPECIFICATIONS:

- Solid state microprocessor with easy access front panel settings
- Front panel display for time of day, days until net regeneration, volume remaining, current flow rate and total volume used (totalizer) and Tank In Service indication
- Four methods to initiate regeneration; meter immediate, meter delayed, time clock delayed or pressure differential
- Optional double backwash feature offers optimum regeneration, cleaning ability and efficiency
- Adjustable cycle times with 6-cycle control delivers controlled backwash, downflow brining, slow rinse, second backwash, fast rinse, refill, and downflow service
- Coin Cell Lithium battery back-up with 8 hour carry over
- Downflow or upflow brining regeneration



Cabinet unit with door open



Cabinet unit with Fleck 5600



Cabinet unit with Clack WS1



Cabinet unit

WATER SOFTENER CABINET

- 12-volt output AC adaptor provides safe and easy installation
- Treated/Soft water post fill and regeneration
- Reliable and proven DC motor, seal spacer stack and piston

FLECK 5600 CONTROL VALVE SPECIFICATIONS:

- Economical low voltage power supply keeps the time and activates the piston/valve mechanics with a single motor
- Simple mechanical design is easy to use
- Two valve body designs: one for downflow regeneration and one for upflow
- Injector/drain modules containing the brine valve, flow controls and injector are removable from the valves exterior
- Ruggedly-built timer is designed with heavy-duty 3/8" wide plastic gears and single motor
- 5600 controls are user-friendly
- Treated/Soft water post fill and regeneration
- Designed with double backwash

DIMENSIONS:



Cabinet Specifications: Light Gray with Dark Gray Trim (Blue trim available), safety overflow prevention brine fill valve. Also available in 18".

OPTIONAL SYSTEMS: SELECT BEST SYSTEM FOR YOUR APPLICATION

Control Valve: Clack WS1 or Fleck 5600 available with either Time Clock or Metered regeneration and optional bypass valve

CONTROL VALVE	SOFTENING CAPACITY	SOFTENING RESIN (CF)	STANDARD CARBON (CHLORINE)	CENTAUR CARBON (CHLORAMINES)	TANK SIZE	SALT CAPACITY
WS1 or 5600	32k	1.0 (CF)	N/A	N/A	10"x35"	258 Lbs.
WS1 or 5600	24k	.75 (CF)	.25 (CF)	N/A	10"x35"	258 Lbs.
WS1 or 5600	24k	.75 (CF)	N/A	.25 (CF)	10"x35"	258 Lbs.
WS1 or 5600	24k	.75 (CF)	.12 (CF)	.13 (CF)	10"x35"	258 Lbs.
WS1 or 5600	24k	.75 (CF)	N/A	N/A	9"x35"	279 Lbs.

*Come visit our showroom
and 20K sq. ft. facility*

1155 Cattlemen Road, Unit B, Sarasota, FL 34232
(941) 341-0847 aqua-wholesale.com